

Bouchons, équerres et vannes

Description	Filetage(s) mâle	Taroudage(s)	Référence	P.U. HT €
Bouchons en laiton filetage gaz BSP - en laiton 	G 1/4" G 3/8" G 1/2" G 3/4" G 1" G 1 1/2"		BP14 BP38 BP12 BP34 BP100 BP112	2,82 4,84 10,19 9,50 15,95 76,65
Équerres femelle/femelle taroudage gaz BSP - en laiton nickelé 		G 1/8" G 1/8" G 1/4" G 1/4" G 3/8" G 3/8" G 1/2" G 1/2" G 3/4" G 3/4" G 1" G 1"	A91818 A91414 A93838 A91212 A93434 A90101	1,48 2,07 2,74 4,41 5,58 9,54
Équerres égales mâle conique filetage gaz BSP - en laiton nickelé 	R 1/8" R 1/8" R 1/4" R 1/4" R 3/8" R 3/8" R 1/2" R 1/2" R 3/4" R 3/4" R 1" R 1"		A3318 A3314 A3338 A3312 A3334 A3301	1,54 2,01 2,74 4,37 5,87 9,54
Équerres mâle conique/femelle filetage gaz BSP - en laiton nickelé 	R 1/8" R 1/4" R 3/8" R 1/2" R 3/4" R 1"	G 1/8" G 1/4" G 3/8" G 1/2" G 3/4" G 1"	A101818 A101414 A103838 A101212 A103434 A100101	1,40 1,87 2,50 3,82 6,09 9,54
Vannes à boisseau sphérique laiton femelle/femelle PN40 (*) 		G 1/4" G 3/8" G 1/2" G 3/4" G 1"	RSI13 RSI17 RSI21 RSI27 RSI34	8,40 8,40 9,17 13,09 19,95
Mini vannes papillon Femelle/Femelle PN16 (**) 		G 1/8" G 1/4" G 3/8" G 1/2"	FSI10 FSI13 FSI17 FSI21	5,04 5,25 5,54 5,85

(*) température d'utilisation : -20°C à +150°C

(**) température d'utilisation : -20°C à 90°C